

PRODUCT INFORMATION

MEDIA GRADE DSR4/220 290W

Description

The filter media is manufactured from non toxic thermally bonded fibre which is built up progressively to form a high density matrix with superb mechanical strength.

Application

Particularly suitable for all air conditioning installations as a pre-filter to more efficient secondary filters and may be used as a pre-filter in paint spray booths.

TECHNICAL DATA

AVERAGE ARRESTANCE	%	92
RATED AIR FLOW	M3/H/M2	5400
INITIAL AIR VELOCITY	M/S	1.5
INITIAL RESISTANCE	Pa	25
FINAL RECOMMENDED RESISTANCE	Pa	210
TEMPERATURE RESISTANCE	Deg C	100
MAXIMUM OPERATING HUMIDITY	% rh	100
FILTER DEPTH	mm	25
WASHABILITY	SEMI-REGENERABLE	
FILTER CLASSIFICATION	G4 BS 6540/PART 1	

<u>FLAME RESISTANCE</u>	BS 5588/CP413	NON COMBUSTIBLE
-------------------------	---------------	-----------------

<u>SPECIAL FEATURES</u>	THERMALLY BONDED FREE OF ALL TOXIC FUME EMISSIONS
-------------------------	---

SUPPLY OPTIONS

ROLL LENGTH	Meters	20
ROLL WIDTH	Meters	2.0

SPECIAL DIMENSIONS AND PADS	TO CUSTOMER'S REQUIREMENTS
-----------------------------	-------------------------------

Prosep Filter Systems Ltd
Unit G19, River Bank Way,
Lowfields Business Park, Elland,
West Yorkshire HX5 9DN

Phone: 01422 377367
Fax: 01422 377369
email: sales@prosep.co.uk
www.prosep.co.uk

for all your filter requirements