

LT Watermakers

400 - 1800 GPD
(1.5 - 6.8 m³/day)



Practical and Reliable Fresh Water Supply

The LT desalinator offers fresh water independence for ocean crossings, extended voyages or cruising where dock water supplies are unreliable.

The units feature a semi modular frame format, for installation flexibility. The frame is compact and can be above or below the water line. The boost pump and prefilters are supplied as loose items.



Offshore Marine LT-1800


Contact Information:

Parker Hannifin Corporation
Racor Division/Village Marine Tec.
2000 W. 135th St.
Gardena, CA 90249

phone 310 516 9911
fax 310 538 3048
racor@parker.com
www.villagemarine.com

www.parker.com/racor

Key Features:



Models 400 and 600 can be configured with membranes mounted on top or back of frame, or with remote membrane rack extending height or depth by 4"/10cm. Please specify when ordering. Other models have remote membrane rack only.



ENGINEERING YOUR SUCCESS.

LT Watermakers

400 - 1800 GPD
(1.5 - 6.8 m³/day)

Standard Features:

- Compact stainless steel high pressure pump is resistant to the corrosive seawater environment
- Sediment prefilter at 5 micron rating

- Magnetic drive low pressure pump provides up to 10 psi of boost pressure to the filtration system. Never requires seal replacement
- Glycerine filled pressure gauges
- Flowmeter to monitor freshwater production
- Freshwater flush system included standard. Optional timed automatic flush with adjustable interval and duration for set-and-forget flushing
- 316 stainless steel pressure regulator is adjustable to allow operation in brackish or fresh water
- Electrical control panel Nema 4X with motor starter and pump controls
- Automatic diversion valve diverts water to overboard if quality drops below acceptable standards
- Digital water quality monitor displays purity of product water produced

Model	Part Number	Power** Volts/Hz/Amps	Dimensions inch/cm	Capacity GPH/LPH	Weight lbs/kg
LT-400	90-6016	110/60/18	*width 19.5/50 depth 16/41 height 12/30	16/63	115/52
	90-6017	220/60/8			
	90-6018	230/50/8			
LT-500	90-6021	110/60/18	400 size plus remote membrane rack, W x H 50x6/127x15	21/80	115/52
	90-6022	220/60/8			
	90-6023	230/50/8			
LT-600	90-6024	110/60/18	*width 19.5/50 depth 16/41 height 12/30	25/95	121/55
	90-6025	220/60/8			
	90-6026	230/50/8			
LT-800	90-6027	110/60/18	400 size plus remote membrane rack, W x H 50x6/127x15	33/126	125/57
	90-6028	220/60/9			
	90-6029	220/50/8			
LT-1000	90-6011	220/60/12	400 size plus remote membrane rack, W x H 50x12/127x30	42/157	135/61
	90-6012	230/50/12.5			
LT-1300	90-6013	220/60/12	400 size plus remote membrane rack, W x H 50x18/127x45	54/205	142/64
	90-6014	230/50/12.5			
LT-1800	90-6015	220/60/12	400 size plus remote membrane rack, W x H 50x22/127x50	75/284	157/71

* Models 400 and 600 membrane rack can be mounted on top or on back of frame, add 4"/10cm to height or depth.

**All units are single phase power only.

Spares and Consumables

Part No.	Description	Part No.	Description
85-0050	Pump Oil, Quart	40-0241	Salinity Probe
33-0117	Prefilter 5 mic (models 400-800)	33-2519	Membrane Element (model 400,600)
33-0052	Prefilter 5 mic (models 1000-1800)	33-2538	Membrane Element (model 500,800,1300,1800)
33-0271	Prefilter O-ring (5 mic models 1000-1800)	90-2512	Membrane O-Ring Kit
33-0311	Flush Filter Element	85-0102	Cleaning Kit
90-0005	Filter O-Ring	85-0103	Preservation Kit

To maintain peak performance always use genuine Parker-Racor/Village Marine Tec. replacement parts. We reserve the right to change our specifications or standards without notice.



PROSEP FILTER SYSTEMS LTD
Unit G19
River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN


Tel: 01422 377367

Fax: 01422 377369

Email: enquiries@prosep.co.uk

www.prosep.co.uk

Map and Directions to Prosep Filters Limited



Leave M62 at Junction 24.

At roundabout adjacent to Cedar Court Hotel take 2nd exit onto dual carriageway (A629), signposted Halifax.

Take 1st exit slip road.

At roundabout at end of sliproad, take 3rd exit off.

This is the entrance to Lowfields Business Park.

Proceed straight over 1st roundabout.

At next roundabout take 2nd exit onto River Bank Way - Prosep Filters can be found on the left after the S-bend.

[Link to Google Maps](#)