

# Salinity Monitor and Diversion Valve

12 Volt DC

Part # 90-0081



Salinity Monitor

## Contact Information:

Parker Hannifin Corporation  
**Racor Division/Village Marine Tec.**  
2000 W. 135th St.  
Gardena, CA 90249

phone 310 516 9911  
fax 310 538 3048  
racor@parker.com  
www.villagemarine.com

[www.parker.com/racor](http://www.parker.com/racor)

Racor Village Marine stand alone Salinity monitor system can be fitted to models Sea Quencher or Little Wonder watermakers or to any make 12 Volt DC model. The compact assembly provides water quality reading and an automatic diversion valve to ensure that only fresh water flows to the potable water storage tank.

## Dimensions

8.5 inch / 22 cm wide  
5 inch / 13 cm high  
3 inch / 13 cm deep



ENGINEERING YOUR SUCCESS.

# Salinity Monitor and Diversion Valve

12 Volt DC  
Part # 90-0081



## Monitor Instructions

Salinity display, as ppm NaCl. Display reads 1 when result is above 2000 ppm.

Press the MEAS button to view the measured salinity. Calibrate by putting probe in a known buffer solution, and turning the CAL potentiometer with a screwdriver.

Press the SET button to view minimum acceptable water quality. Adjust by turning the tiny potentiometer marked SET with a screwdriver. Recommended setting 500, meaning water above 500 ppm is rejected overboard.



Over-ride Switch. Set to the Auto position for normal operation. Set to OFF to keep Product Solenoid Valve closed, for instance when flushing out cleaning chemicals or for 10 minutes when first installing new membranes.

Set to ON to keep Product Solenoid Valve open, for instance when it is desired to override the quality reading from the probe or for troubleshooting.

LED lamp lights yellow when water is "good" quality (below setpoint). Lamp is green when water quality is "bad" (above setpoint)

To maintain peak performance always use genuine Parker-Racor/Village Marine Tec. replacement parts. We reserve the right to change our specifications or standards without notice.

© 2010 Parker Hannifin Corporation

Print Reorder Number 7956 Rev 10-01-2010



ENGINEERING YOUR SUCCESS.

PROSEP FILTER SYSTEMS LTD  
Unit G19  
River Bank Way  
Lowfields Business Park  
Elland  
West Yorkshire  
HX5 9DN

**Tel: 01422 377367**

**Fax: 01422 377369**

Email: [enquiries@prosep.co.uk](mailto:enquiries@prosep.co.uk)

[www.prosep.co.uk](http://www.prosep.co.uk)

**Map and Directions to Prosep Filters Limited**



Leave M62 at Junction 24.

At roundabout adjacent to Cedar Court Hotel take 2nd exit onto dual carriageway (A629), signposted Halifax.

Take 1st exit slip road.

At roundabout at end of sliproad, take 3rd exit off.

This is the entrance to Lowfields Business Park.

Proceed straight over 1st roundabout.

At next roundabout take 2nd exit onto River Bank Way - Prosep Filters can be found on the left after the S-bend.

[Link to Google Maps](#)