


Oilblock Absorption Cartridge

Free and emulsified oil removal



OILBLOCK™ absorption cartridges are specifically manufactured for the high efficiency removal of free dispersed oils from water. Typical applications include bilge water treatment, contaminated surface run-off water and many other similar industrial process applications. The cartridges employ a proprietary modified polymer that both absorbs and chemically binds the hydrocarbon molecules into its interior matrices, the oil cannot be released once absorbed. Consequently these properties make Oilblock cartridges an effective absorbent for free emulsified and dissolved oils, synthetic lubricants, grease and a multitude of organic solvents.



Contact Information

Twin Filter BV
A Parker Hannifin company
Zuiddijk 398
1505 HE Zaandam
The Netherlands

phone +31 756 555 000
fax +31 756 555 015
twinfilter.info@parker.com

www.parker.com/processfiltration
www.twinfilter.com

Benefits

- 99% removal of oils in a single pass.
- Cartridge blocks after saturation and no hydrocarbon bypass is possible.
- The absorption capacity can be up to 4 times its own weight.
- No direct contact with saturated media during handling.
- High flow rates.
- Specially designed for the offshore industry.
- Reliable and simple solution.
- Easy handling and operation.
- Fit into existing cartridge filter units.
- Manufacturing process eliminates voids in media and thus bypass issues.

Applications

- Mud pit cleaning
- Produced water
- Displacement clean up
- Acid flow back
- Completion fluids
- Pipeline, system purge & hydro test discharges
- Ballast and bilge water
- Run-off water



ENGINEERING YOUR SUCCESS.

Oilblock Absorption Cartridge

SPECIFICATIONS

Materials of Construction

Type of Construction

- Integrally sealed, oilblock media supported by polypropylene construction.

Filter Media

- Oilblock™

Media Support Core

- Molded polypropylene

Media Support Cage and Thermally

Welded End Caps

- Molded polypropylene

Dimensions

Cartridge Outside Diameter

- 2.5" (64 mm)

Cartridge Inside Diameter

- 1.1" (28 mm)

Cartridge Length

- 40" (1005 mm)

Connection

- Type 222 (code 3)

Media Weight per Cartridge (40")

- 1.6 lbs (0,7 kg)

Maximum Recommended Operating Conditions

Temperature

- 140°F (60°C)

Allowable ΔP

- 36.3 psi (2,5 bar)

Flow Rate

- 6.29 bbl/hr (1 m³/hr) per 40" length

pH Range

- 1 - 9

Recommended Operating Conditions

Required Pre Filtration

- 25 micron, depth filter

Absorption Capacity

- Max. 2 kg of hydrocarbons per cartridge (40")

End Cap Configuration

222 O-rings & Flat End Cap



Article description

TFOB

Nominal Length			End Cap Configuration		Flow Direction	
Code	Inch	mm	Code	Description	Code	Description
40	40	1005	2OF	222 O-ring/flat	RF	Radial flow
Others on request			Others on request			

Specifications are subject to change without notification.
For User Responsibility Statement, see www.parker.com/safety

© 2013 Parker-Hannifin Corporation
Twin Filter BV
All Rights Reserved



PROSEP FILTER SYSTEMS LTD
Unit G19
River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN

Tel: 01422 377367

Fax: 01422 377369

Email: enquiries@prosep.co.uk

www.prosep.co.uk

Map and Directions to Prosep Filters Limited



Leave M62 at Junction 24.

At roundabout adjacent to Cedar Court Hotel take 2nd exit onto dual carriageway (A629), signposted Halifax.

Take 1st exit slip road.

At roundabout at end of sliproad, take 3rd exit off.

This is the entrance to Lowfields Business Park.

Proceed straight over 1st roundabout.

At next roundabout take 2nd exit onto River Bank Way - Prosep Filters can be found on the left after the S-bend.

[Link to Google Maps](#)