

PRODUCT INFORMATION

FILTER MEDIA GRADE DSR6/220 290BW

Description

The filter media is manufactured from non toxic thermally bonded fibre which is built up progressively to form a high density matrix with superb mechanical strength. Blue on air in side and white on air exit face.

Application

Particularly suitable for all air conditioning installations as a pre-filter to more efficient secondary filters and may be used as a pre-filter in paint spray booths.

TECHNICAL DATA

AVERAGE ARRESTANCE	%	91
RATED AIR FLOW	M3/H/M2	5400
INITIAL AIR VELOCITY	M/S	1.5
INITIAL RESISTANCE	Pa	25
FINAL RECOMMENDED RESISTANCE	Pa	210
TEMPERATURE RESISTANCE	Deg C	100
MAXIMUM OPERATING HUMIDITY	% rh	100
FILTER DEPTH	mm	25
WASHABILITY	SEMI-REGENERABLE	
FILTER CLASSIFICATION	G4	
	BS 6540/PART 1	

FLAME RESISTANCE BS 5588/CP413 NON COMBUSTIBLE

SPECIAL FEATURES THERMALLY BONDED
FREE OF ALL TOXIC
FUME EMISSIONS

SUPPLY OPTIONS

ROLL LENGTH	Meters	20
ROLL WIDTH	Meters	2.0

SPECIAL DIMENSIONS AND PADS TO CUSTOMER'S
REQUIREMENTS

Prosep Filter Systems Ltd
Unit G19, River Bank Way,
Lowfields Business Park,
Elland, West Yorkshire
HX5 9DN

Phone: 01422 377367
email: sales@prosep.co.uk
www.prosep.co.uk



for all your filter requirements