



Simplex Basket Strainers

1/2" to 8" - PVC, Corzan® CPVC and Eastar® Clear Polyester



6" and 8" Design

Features

- External Body Threads
- Low Pressure Drop
- Wide Choice of Baskets
- In-line or Loop Piping Design
- True Union Connections
- Ergonomic Hand Removable Cover
- FPM Seals
- Integral, Flat Mounting Base
- Hand Removable Vent On Cover
- Hand Removable Drain On Body
- Liquid Displacing Cover

Corzan® is a registered trademark of Noveon, Inc.
Eastar® is a registered trademark of Eastman

Options

- Stainless Steel Mesh Strainer Baskets
- EPDM Seals

Protect System Components

When pipeline system components require protection from dirt and debris and the line can be shut down for basket cleaning, a Hayward All Plastic Simplex Basket Strainer is the ideal choice. Unwanted particles are removed as the process media passes through a perforated strainer basket contained inside the strainer body. The basket traps the unwanted material while allowing the process media to flow freely.

Easy Basket Cleaning

Changing or cleaning the strainer basket is quick and easy. The hand removable, spin-off cover features two angled handles for easy access to the strainer basket. The housing features external cover threads that do not contact the process media and never need cleaning. Venting and draining are made possible by two hand removable, threaded plugs, one on the top of the cover and the other on the housing side.


Choice of Piping Connections

Hayward Simplex Basket Strainers can be installed either in-line or with loop piping configurations. This is made possible by a unique design that incorporates three piping connections on the strainer body that are used as inlets and outlets. The unused connection is plugged using a blind fitting (included). True union connections make it possible to remove the strainer from the piping system without disassembling the piping connections.

Wide Range of Strainer Baskets

Plastic baskets in perforation sizes from 1/32" to 3/16" are available. Stainless steel perforated baskets are available from 1/2" to 1/32". Mesh stainless steel baskets for very fine straining applications are available in sizes from 20 mesh down to 325 mesh.

Technical Information



Size	Dimensions - Inches / Millimeters									WEIGHT		VOLUME
	a	b	c	d	e	f	j	k	Skt/Thd	Flange	GAL / LT	
1/2"	8.64 / 219	9.63 / 245	11.0 / 279	2.25 / 57	6.75 / 171	4.31 / 109	8.00 / 203	10.77 / 274	8.0 / 3.4	9.0 / 4	0.20 / 0.8	
3/4"	8.64 / 219	9.63 / 245	11.0 / 279	2.25 / 57	6.75 / 171	4.31 / 109	8.00 / 203	11.02 / 280	8.0 / 3.4	9.0 / 4	0.20 / 0.8	
1"	8.64 / 219	9.63 / 245	11.0 / 279	2.25 / 57	6.75 / 171	4.31 / 109	8.00 / 203	11.64 / 296	8.0 / 3.4	9.0 / 4	0.20 / 0.8	
1-1/4"	12.75 / 324	13.38 / 340	13.5 / 343	3.25 / 83	9.5 / 241	6.13 / 156	12.86 / 327	15.63 / 397	14.0 / 6.4	16.5 / 7.5	0.70 / 2.7	
1-1/2"	12.69 / 322	13.38 / 340	13.5 / 343	3.25 / 83	9.5 / 241	6.13 / 156	12.86 / 327	15.89 / 404	14.0 / 6.4	16.5 / 7.5	0.70 / 2.7	
2"	12.75 / 324	13.38 / 340	13.5 / 343	3.25 / 83	9.5 / 241	6.13 / 156	12.86 / 327	16.29 / 414	14.0 / 6.4	16.5 / 7.5	0.70 / 2.7	
2-1/2"	16.52 / 384	19.83 / 504	16.0 / 406	4.83 / 123	14.83 / 377	7.25 / 184	17.25 / 438	21.02 / 534	28.0 / 13	33.0 / 15	2.80 / 10.6	
3"	16.40 / 384	19.83 / 504	16.0 / 406	4.83 / 123	14.83 / 377	7.25 / 184	17.25 / 438	20.36 / 517	28.0 / 13	33.5 / 15	2.80 / 10.6	
4"	17.27 / 384	19.83 / 504	16.0 / 406	4.83 / 123	14.83 / 377	7.25 / 184	17.25 / 438	22.13 / 562	28.0 / 13	37.0 / 17	2.80 / 10.6	
6"	n/a	34.28 / 871	18.0 / 457	10.66 / 271	27.19 / 691	11.75 / 298	21.80 / 554	22.42 / 569	n/a	60.0 / 27	6.8 / 25.7	
8"	n/a	34.28 / 871	18.0 / 457	10.66 / 271	27.19 / 691	11.75 / 298	28.75 / 730	25.19 / 640	n/a	80.0 / 36	9.0 / 34.1	

Cv Factors

Size	Factor	Size	Factor
1/2"	15	2-1/2"	290
3/4"	18	3"	300
1"	20	4"	350
1-1/4"	55	6"	1000
1-1/2"	58	8"	750
2"	60		

The above Cv Factors were determined using a 1/16" perforated plastic basket in 1/2" through 4" strainers and a 5/32" perforated stainless steel basket in 6" and 8" strainers. For other size basket perforations, multiply by the correction factor in the above Correction Factor charts.

Pressure Drop Calculations

Basket Perforation Correction Factors

For 1/2" to 4" Strainers


Plastic Baskets		Stainless Steel Baskets	
1/32"	1.05	1/32"	.82
1/16"	1.00	3/64"	.63
1/8"	.58	1/16"	.74
3/16"	.46	5/64"	.50
		7/64"	.51
		1/8"	.58
		5/32"	.37
		3/16"	.46
		1/4"	.58

For 6" to 8" Strainers

Plastic Baskets		Stainless Steel Baskets	
1/8"	2.00	1/32"	2.25
3/16"	1.50	3/64"	1.73
		1/16"	2.03
		5/64"	1.37
		7/64"	1.40
		1/8"	1.58
		5/32"	1.00
		3/16"	1.26
		1/4"	1.58

The pressure drop across the strainer, for water or fluids with a similar viscosity, can be calculated using the formula at the right: $\Delta P = \left[\frac{Q}{Cv} \right]^2$ Where ΔP = Pressure Drop, Q = Flow in GPM, Cv = Flow Coefficient

Operating Temperature/Pressure



Selection Chart

Size	Material	End Connection	Seal*	Rating
1/2" to 4"	PVC, CPVC	Thd, Skt, Flg	FPM	150 PSI @ 70F
1/2" to 2"	EASTAR®	Thd, Skt, Flg	FPM	100 PSI @ 70F
6" to 8"	PVC, CPVC	Flg	FPM	150 PSI @ 70F

*EPDM seals POA.

Basket Selection

- The 1/2" to 1" strainers can be ordered with either a 1/32" or 1/16" perf plastic basket.
- The 1-1/2" and 2" with a 1/32", 1/16", 1/8", or 3/16" perf plastic basket.
- The 3" and 4" with a 1/16", 1/8" or 3/16" perf plastic basket.
- The 6" and 8" with a 1/8" or 3/16" perf plastic basket.
- Stainless steel baskets for all size strainers are available in these perms: 1/32", 3/64", 1/16", 5/64", 7/64", 1/8", 5/32", 3/16", 1/4", 3/8", 1/2"; and in mesh sizes: 20, 40, 60, 80, 100, 200, 325



Hayward Industrial Products, Inc.

One Hayward Industrial Drive, Clemmons, NC 27012
 Tel: 1-888-429-4635 (1-888-HAYINDL) • Fax: 1-888-778-8410
 E-mail: hflow@haywardnet.com
 Web Site: http://www.haywardindustrial.com

PROSEP FILTER SYSTEMS LTD
Unit G19
River Bank Way
Lowfields Business Park
Elland
West Yorkshire
HX5 9DN

Tel: 01422 377367

Fax: 01422 377369

Email: enquiries@prosep.co.uk

www.prosep.co.uk

Map and Directions to Prosep Filters Limited



Leave M62 at Junction 24.

At roundabout adjacent to Cedar Court Hotel take 2nd exit onto dual carriageway (A629), signposted Halifax.

Take 1st exit slip road.

At roundabout at end of sliproad, take 3rd exit off.

This is the entrance to Lowfields Business Park.

Proceed straight over 1st roundabout.

At next roundabout take 2nd exit onto River Bank Way - Prosep Filters can be found on the left after the S-bend.

[Link to Google Maps](#)