500 Series

500 Series Overview



Specifications	WFH500	WFH525	WFH525/ACV	525EHA
Flow Rate	120 GPH (454 GPH)	120 GPH (454 GPH)	120 GPH (454 GPH)	120 GPH (454 GPH)
Fuel Port Size	1/2 NPT	1/2 NPT	1/2 NPT	1/2 NPT
Coolant Port Size	N/A	1/2 NPT	1/2 NPT	1/2 NPT
Width	5.3 in. (13.5 cm)	5.3 in. (13.5 cm)	5.3 in. (13.5 cm)	5.3 in. (13.5 cm)
Depth	5.3 in. (13.5 cm)	5.3 in. (13.5 cm)	5.3 in. (13.5 cm)	5.3 in. (13.5 cm)
Height	15.8 in. (40.1 cm)	15.8 in. (40.1 cm)	15.9 in. (40.3 cm)	15.9 in. (40.3 cm)
H ₂ O Removal	99%	99%	99%	99%
Coolant Ports	No	Yes	Yes	Yes
Heater Ports 12 vdc Pre-heater 120 vdc Pre-heater	Yes No	No No	No No	No Yes
Automatic Coolant Valve (ACV)	No	No	Yes	Yes
Service Element	4 in.	4 in.	4 in.	4 in.
Operating Temperature	-40° to +255°F (-40° to +124°C)			





enquiries@prosep.co.uk

WE ARE YOUR '**ONE STOP SHOP**' FOR ALL OF YOUR FILTRATION REQUIREMENTS

LIQUID FILTRATION

- CARTRIDGES
- FILTER BAGS
- VESSELS
- STRAINERS

AIR FILTRATION

- VENT FILTERS
- STERILE AIR
- VACCUM
- AIR-CONDITIONING
- FILTER MEDIA

DOMESTIC

- ULTRAVIOLET
- TREATMENT OF BOREHOLES,
- SPRINGS & WELLS
- WATER TESTING

FUEL FILTRATION

DIESEL, AVIATION



Prosep Filter Systems Ltd Unit G19, River Bank Way, Lowfields Business Park, Elland, West Yorkshire HX5 9DN Phone: 01422 377367 email: sales@prosep.co.uk www.prosep.co.uk



for all your filter requirements

PROSEP

FILTER SYSTEMS LTD