

SELF CLEANING FILTER



SPECIFICATIONS

- Option 1/2" or 3/4" BSP with brass insert
- Hot water kit suitable for 8.6 bar at 93 deg C
- Cold water kit suitable for 6 bar at 45 deg C
- Wall mounting bracket and bowl spanner included.
- Optional cartridge range

This is a filter kit designed to be fitted with a mesh filter cartridge that is suitable for removing silt, scale and rust particles from hot or cold water by opening the valve in the base of the unit accumulated dirt is flushed away to drain, when the valve is closed normal flow is resumed. In its kit form this filter unit may be supplied without the mesh cartridge or with a choice of washable 50, 100 or 150 micron nylon mesh screens.

Order code	Description
FHPR123V-R	Cold water filter kit 1/2" BSP without element
FHPR123V-R**M	Cold water filter kit 1/2" BSP with mesh. ** insert 80 or 250
FHPR343V-R	Cold water filter kit 3/4" BSP without element
FHPR343V-R**M	Cold water filter kit 3/4" BSP with mesh. ** enter 80 or 250
F10NN2PC-VR	Hot water filter kit 3/4" BSP without element
F10NN2PC-VR**M	Hot water filter kit 3/4" BSP with mesh. ** enter 50,100 or 150

Spare Filter elements

Cold Water

80 micron screen	A4030030C
250 micron screen	A4030120C



Hot water

50 um	FCPHH50M
100 um	FCPHH100
150um	FCPHH150M



Hot water elements also fit the cold water housing for increased micron range

Prosep Filter Systems Ltd
Unit G19, River Bank Way,
Lowfields Business Park, Elland,
West Yorkshire HX5 9DN

Phone: 01422 377367
Fax: 01422 377369
email: sales@prosep.co.uk
www.prosep.co.uk

for all your filter requirements